

## 1U 19" & ETSI Swing Type Fiber Optic Patch Panel CAN-PVT-50X

### Overview

Ensures professional cable management and ease of fiber termination with front cable manager for patchcords

### Highlights

- ✓ 1U version 24 ports capacity (up to 30 ports)
- ✓ Swing Out system with front cable management for patchcords
- ✓ Manages small & large quantities of fiber with a high packing density
- ✓ Cable glands to secure the incoming fiber, allows min movement
- ✓ Fiber guide tubes to protect and direct the fibers to the cassettes in a professional way
- ✓ Minimum bend radius of fibers and strain relief for all entry cables
- ✓ Fiber bend radius control - < 35mm
- ✓ All known connector types such as SC, FC, ST, E2000, LC, MU etc. are possible.

### Density Information

1U 24 ports Module: 24 pieces SC/LC/FC/ST/E200/DIN/MU-PC/APC etc. simplex adapters and 24 pieces 1.5 m SC/LC/FC/ST/E200/DIN/MU-PC/APC simplex pigtail (confirms G652, G652D standards)

### Technical Details

<b>Dimensions</b>	430 mm (W) x 280 mm (D) x 1U (H)
<b>Compliance</b>	GR-449-core of Telcordia Specification
<b>Finish</b>	Powder coat RAL7032
<b>Weight</b>	1U : 2.1 kg, 2U : 2.8 kg
<b>Material</b>	Aluminum

### Applications

Fiber Transmission Networks in Telco's Central applications, Fiber exchange systems, Utility Networks

