Pretium® Connector Housing (PCH)

2 rack unit, holds 4 CCHE Panels + MFT Tray holder with 4 MFT Trays capacity



The rack-mount Pretium® Connector Housings (PCH) are available in 1U, 2U and 4U sizes and mount in 19-in racks or cabinets. Combined with the modules, panels, harnesses, trunks and jumpers, they provide a tip-to-tip solution for your fibre optic network.

Features and Benefits

Compatible with Plug & Play™ Systems modules
Designed to support Plug & Play Systems applications

Splice in the housing

Saves rack space and the cost of the second housing

Removable top (1U, 2U)

Maximizes ease of access

Transparent front door (04U and 02U)

Permits viewing while protecting installed patch cords

Large removable fiber guides in front

Effectively manage high patch cord densities

Standards

RoHS Free of hazardous sub-

stances according to RoHS

2002/95/EG

UL-Listed

Specifications

| General Specifications | |
|------------------------|----------------------------------|
| Application | Enterprise Networks, Data Centre |
| Mounting Type | Rack 19", Rack 23" |
| Product Type | Rack-Mountable Hardware |
| Mounting Technology | Protruding |
| Access Type | Front access fixed |
| Lockable | yes, front and rear side |



Pretium® Connector Housing (PCH)

2 rack unit, holds 4 CCHE Panels + MFT Tray holder with 4 MFT Trays capacity



| Design - Hardware | |
|-------------------|--------------------|
| Housing Type | PCH |
| Height Unit | 2U |
| Cable entry type | slotted |
| Splice Tray Type | MFT |
| Housing Material | Metal |
| Housing Colour | Dark metallic grey |

| Mechanical characteristics | |
|----------------------------|-------------------------|
| Dimensions (HxWxD) | 90 mm x 430 mm x 420 mm |
| Weight | 5.9 kg |

Ordering Information

| Part Number | PCH-02U-SPL |
|---------------------|---|
| Product Description | PCH Housing, 2U, dark metallic grey, 4 CCHE Panels capacity + MFT Tray holder with 4 MFT Trays capacity |

Shipping Information

| Packing dimensions (L x W x H) | 600 mm x 580 mm x 160 mm |
|--------------------------------|--------------------------|
| Shipping Weight | 9.5 kg |
| Units per Delivery | 1/1 |



Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · www.corning.com/cablesystems/emea

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/emea/trademarks. Corning Cable Systems is ISO 9001 certified. © 2013 Corning Cable Systems. All rights reserved.

