

Fiber Optic Video & Data Transmission for PTZ Cameras 8-Channel Video + 1 Return Rs485 Data over Fiber

8 →
Video

System Design

Fiber Optic Video & Data Transmitter & Receiver

VOS-8010FBT/R can transmission 8-Channel digital composite video and 1 return rs485 data. It is designed for PTZ cameras.

Stand-alone or rack-mount. All units of VOS-8010FBT/R come in an insert card version. The cards can be inserted into our 14-slot,19inch 4U or 6U rack-mountable card cage (VOS-CH04 or VOS-CH06). One 8-Channel video card require **two slots widths**.

Single-Mode or Multi-Mode,VOS-8010FBT/R can support FC/PC or ST/PC Optical connector, can be used in Daisy-Chain system (Need to customize). The Transmission distance range according to the Optical Budget. Manufacturer's standard is: Single-mode 20km or Multi-mode 1.2km.



Audio


← **1**
Data

Ethernet

Features

- Support Point-to-Point or Daisy-Chain connection
- Uncompressed Digital Composite Video over one fiber
- Compatible with all PAL, NTSC,SECAM Video Systems
- Multi-mode Fiber Support for Distances up to 1.2 km
- Single-Mode Fiber Support for Distances up to 100 km
- LED Status Provide Rapid Indication of Operating Parameters
- No EMI or RFI and no ground loops
- Stand alone or rack-mount
- Produce according to customer's specifications,providing OEM

Typical Configuration



Video & Data over Fiber

Ordering Information

Model Number		Fiber Mode	Wavelengths	Optical Power Budget	Maximum Transmission Distance
Transmitter	Receiver				
VOS-8010FBMT	VOS-8010FBMR	Multi-Mode	1310nm/1550nm	10dB	1.2km
VOS-8010FBST	VOS-8010FBSR	Single-Mode	1310nm/1550nm	12dB	20km
VOS-8010FBST-4	VOS-8010FBSR-4	Single-Mode	1310nm/1550nm	18dB	40km
VOS-8010FBST-6	VOS-8010FBSR-6	Single-Mode	1310nm/1550nm	25dB	60km

Note:

- The Optical Power Budget data fit Multit-mode(62.5/125 μ m),Single-Mode(9/125 μ m).
- When using 50/125 μ m multimode fiber, subtract 3 dB from the optical power budget.
- Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.
- Maximum transmission distance is also limited by fiber bandwidth.
- Power adapter is manufactured by third party and is supplied with fitted screw-terminal output cables. Power adapter included (for standalone) US, European, UK or Australian power plug.
- Please feel free to consult factory for any special requirement and customization

Specification

<p>• Video</p> <p>Number of Channels: 8-Channel Video Input/output impedance: BNC 75Ω Input/output Compatibility: PAL, NTSC, SECAM Input/output voltage: 1.0 Volt p-p Bandwidth: 6.5MHZ Bit Resolution: 8-Bit Digital Transmission Differential Gain: < 1.5% Differential Phase: < 1.5° Tilt: < 5% Signal-to-Noise Ratio(SNR): > 67 dB</p> <p>• Data</p> <p>Data Formats: Rs485 Data Rate: DC to 115.2Kbps Bit Error Rate: 10E-9</p>	<p>• Connectors</p> <p>Video: 75Ω BNC (Gold Center Pin) Data: Terminal Block Optical: FC/PC or ST/PC Optional Stand-Alone Power: Screw terminal block Rack Power: AC line cord</p> <p>• Electrical & Mechanical</p> <p>Input Power Requirements: DC 5V@3A Power Adapter: AC 100V~240V Power Consumption: < 5W Stand-Alone Dimensions: 176.5mm \times 158mm \times 36mm Card for 4U Rack Dimensions: 145mm \times 170mm \times 45.4mm Shipping Weight: 2.5kg (include TX & RX)</p> <p>• Environmental</p> <p>Operating Temperature: -45° C~+75° C Storage Temperature: -45° C~+85° C Relative Humidity: 0%~95% (non-condensing) MTBF: >100,000 hours</p>
---	--